

## Safety Standards that require proof of compliance to be submitted

(Note: if there is any uncertainty whether a standard applies, please contact NMEDA)

F/CMVSS 110 **	<b>Tire Selection and Rims</b> (** show label in test reports or provide identified photo or schematic separately with test reports)
F/CMVSS 206 **	<b>Door Locks / Retention Components</b> (** Compliance submission is postponed until further notice, MFGs may <b>voluntarily</b> submit compliance and will be posted)
F/CMVSS 207	<b>Seating Systems</b>
F/CMVSS 208 **	<b>Occupant Crash Protection (Side Entry Only)</b> (** Includes 50 <sup>th</sup> percentile male dummies test and 5 <sup>th</sup> percentile female dummies test, and seat belt requirements)
F/CMVSS 210	<b>Seat Belt Anchorages</b>
F/CMVSS 214 **	<b>Side Impact Protection</b> (** can be combined with 301 "Fuel System Integrity")
F/CMVSS 225	<b>Child Restraints (Canada 210.1 &amp; .2)</b>
F/CMVSS 301/305**	<b>Fuel System Integrity / Electrolyte Spillage &amp; Shock</b> (** 305 will be posted if submitted)
F/CMVSS 302	<b>Flammability of Materials</b> (full test report or proof of non-ignitable or self-extinguishing materials)
CARB E.O. **	<b>California Air Resources Board Executive Order</b> (** Applies to MFGs selling to CARB required states, otherwise waiver)
49 CFR Part 38.23 (b)	<b>Ramp Design Load (600 lbs.)</b> (Provide test report)
SAE J2093 **	<b>Durability Test / Power Operated Ramps (4,400 min)</b> (** NMEDA version adopted for power ramps. Does not apply to manual ramps)
WTORS C-10	<b>Wheelchair Tie-down and Occupant Restraint</b> (current test report with SAE surrogate wheelchair)