

Vehicle load carrying capacity (Occupants + cargo): 488 Kg (1,077 lbs.) **Seating capacity (maximum as tested):** 6 (including wheelchair positions)

Vehicle alterations as tested	Certification of the following F/CMVSS (*) was reviewed
<ul style="list-style-type: none"> • Full lowered floor (front foot well to in front of rear axle) • Maximum 12inch drop • Passenger side in-floor power ramp • Fold-out manual ramp - optional • Relocated aft-of-axle aftermarket fuel tank • Hydraulic vehicle lowering system – optional • Power sliding door • Tested without trailer hitch receiver • Wheelchair & occupant restraint systems – Q’straint 	<ul style="list-style-type: none"> • F/CMVSS 207/210 (seats and seat belt anchorages) • F/CMVSS 208 (occupant protection) • FMVSS 301 (fuel system integrity) • FMVSS 225, CMVSS 210.1 and 210.2 (child restraint Systems) • F/CMVSS 206 (door locks and door retention components - latches and hinges) • F/CMVSS 302 (flammability) for non-ignitable and self-extinguishing materials only • F/CMVSS 110 (tire selection and rims – tire placard) • 49 CFR 38.23(b) (ramp design load) • SAE J2093 (durability test – power ramps) • CARB executive order • WTORS C-10 (wheelchair tie-downs and occupant restraint systems)
<p>* specific requirements of each standard that was reviewed are listed in the Vehicle Description Form and on the NMEDA web site</p>	

Seating and wheelchair positions			
Row	Driver side	Center	Passenger side
Front	<ul style="list-style-type: none"> • Removable Braun base with OEM bucket seat • Wheelchair position 	N/A	<ul style="list-style-type: none"> • Removable Braun base with OEM bucket seat • Wheelchair position
Second	<ul style="list-style-type: none"> • Wheelchair position 	Wheelchair position	<ul style="list-style-type: none"> • Wheelchair position
Rear	<ul style="list-style-type: none"> • Remounted OEM 3 position 60/40 bench seat 		